

China Advantage Products Cylinder Gas High Purity 99.995% Sf6 Sulfur Hexafluoride

Basic Information

Place of Origin: China
Brand Name: CMC
Certification: COA
Model Number: SF6
Minimum Order Quantity: 1kg

Price: US \$ 9.5/kg
Packaging Details: Cylinder/Tank
Delivery Time: 15 days
Payment Terms: L/C, T/T

• Supply Ability: 5000 Tons/Year



Product Specification

Cylinder Standard:

Product Name: Sulfur Hexafluoride
Valve: Qf-2/Cga 580
Melting Point: -50.8 °C
Boiling Point: -63.8 °C
Cylinder Pressure: 15MPa/20MPa
Purity: 99.999%

Specification: 40L, 47L, 50L, 500L

GB/DOT

Trademark: CMC
 Origin: China
 HS Code: 28129019
 Supply Ability: 5000tons/Year
 CAS No.: 2551-62-4
 Formula: Sf6
 EINECS: 219-854-2



More Images



Product Description

Product Description

Sulfur hexafluoride (SF6) is a colorless, odorless, non-toxic, and non-flammable gas. It belongs to the group of sulfur fluorides and is composed of one sulfur atom and six fluorine atoms bonded together in a octahedral shape. SF6 has a high density, which makes it useful for a variety of applications.

Here are some key points about sulfur hexafluoride gas:

Electrical Industry: SF6 is widely used as an electrical insulating gas in high-voltage power transmission and distribution systems. It provides excellent dielectric properties, allowing for compact designs and efficient electrical insulation.

Circuit Breakers: SF6 is commonly used in circuit breakers to extinguish the electrical arc when the contacts inside the breaker separate. It has a high arc-quenching capability, enabling efficient interruption of electrical currents.

Magnesium Processing: SF6 is used as a protective gas in magnesium smelting processes. It prevents the formation of magnesium oxide on the surface of molten magnesium, ensuring high-quality production.

Medical Applications: SF6 has medical applications as a contrast agent in ultrasound imaging. It is used to improve the visibility of organs and structures during certain diagnostic procedures.

Tracer Gas: Due to its inert nature and high density, SF6 is used as a tracer gas in various applications. It is employed to analyze ventilation systems, detect leaks, and study airflows in confined spaces.

Environmental Concerns: SF6 is a potent greenhouse gas with a global warming potential (GWP) of 23,500 times that of carbon dioxide (CO2) over a 100-year period. Consequently, there is increasing concern about its impact on climate change. Efforts are being made to reduce SF6 emissions and find alternative technologies.

It's important to handle SF6 with caution, following safety guidelines and regulations, as it is a compressed gas and can displace oxygen in confined spaces. Proper storage, transport, and disposal methods should be adhered to when working with SF6.

Basic Info

DOT Class2.2Un NumberUn 1080Cylinder StandardDOT/ISO/GBCylinder Pressure15MPa/20MPaValveQf-2, Cga590Melting Point-50.8 °CAppearanceColorless, OdorlessBoiling Point-63.8 °CDensity6.0886 Kg/M³Molecular Weight146.05

Transport Package 40L, 47L, 50L, 500L Specification 99.995%, 99.999%

Trademark CMC Origin China
HS Code 28129019 Production Capacity 5000tons/Year

Specifications

Specifications	Company Standard
SF6	≥ 99.995%
Air	≤ 10 ppm
CF4	≤ 2 ppm
C2F6	≤ 20 ppm
C3F8	≤ 5 ppm
Low Sulfide	Not Detected
H2O	≤ 1 ppm
Acidity as HF	≤ 0.1 ppm
Hydrolysable Fluor ides as HF	≤ 0.3 ppm
Mineral Oil	≤ 1 ppm

Detailed Photo



Company Profile



Shanghai Kemike Chemical Co., Ltd is staffed by trained personnel, combine many years experience in Gas industry .We supply cylinder gas, electronic gas, etc., and the gas holder, panel, valves and fittings and other equipment, parts and engineering services to our customers in China and worldwide; The products are involved in various industrial fields, such as semiconductor chip, solar cell, LED, TFT-LCD, optical fiber, glass, laser, medicine, etc., Our mission is to partner with our global customers to provide support, solutions and quality products that are innovative, reliable, and safe.

Our products mainly include: H2, O2, N2, Ar, CO2, propane, acetylene, helium, laser mixed gas, SiH4, Sih2cl2, SiHCL3, SiCL4, NH3, CF4, NF3, SF6, HCL, N2O, doping mixed gas (TMB, PH3, B2H6) and other electronic gases.

CH3F F6+CI2 WF6 SiCI4 NH3 NH3 SiH4 Kr H₂S

C2 C3F8 C3F8 **TEOS** CH4 PH₃ SF6 HCI+Ne 4MS

SiH2 CF4 C4F8

SiF4 **C3H8** CI2

DCE BBr3 **C3H6**

POCI3 SO2 N2

BCI3 D2 CO₂

SiHCI3 CH2F2 HF

TMAI DMZn DEZn AsH3

GeH4

C2H4

C2H6

B2H6

C2H2

H2Se

HBr

GeCl4

COS

Xe+NO

TMB+H2

He +As

Ge+Se

D+B

CO+NO

Ar+O2





