

The production of superalloys Semiconductor Industry application Tungsten Hexafluoride

Basic Information

. Place of Origin: China Brand Name: CMC COA · Certification: Wf6 Model Number: Minimum Order Quantity: 1 Piece • Price: US \$ 15/PC Cylinder/Tank · Packaging Details: • Delivery Time: 15 days Payment Terms: L/C, T/T . Supply Ability: 200 Tons/Year



Product Specification

Product Name: Tungsten Hexafluoride

Appearance: Colorless Wf6 Gas Model No.: • Transport: By Sea • Purity: 99.999% • Transport Package: 200t/Year 200t/Year Specification: CMC Trademark: · Origin: China . HS Code: 2812190091 • Supply Ability: 200t/Year · CAS No.: 7783-82-6 Formula: Wf6 • EINECS: 232-029-1



Tungsten Hexafluoride

More Images

Constituent:





Industrial Pure Air

Product Description

Product Description

WF6 refers to tungsten hexafluoride, a chemical compound composed of one tungsten atom bonded to six fluorine atoms. Here are some key points about WF6:

Chemical Formula: WF6

Molecular Weight: 297.83 g/mol

Structure: WF6 has an octahedral molecular geometry, with the tungsten atom at the center and six fluorine atoms arranged around it.

Physical Properties: Tungsten hexafluoride is a colorless gas at room temperature. It has a strong, pungent odor and is highly reactive.

Reactivity: WF6 is a highly reactive compound and readily reacts with water, oxygen, and other substances. It is a strong oxidizing agent and can react violently with reducing agents.

Uses: Tungsten hexafluoride has various applications in the semiconductor industry. It is used in the deposition of tungsten metal thin films during the fabrication of integrated circuits. WF6 is also used in the production of tungsten hexafluoride-based compounds, such as tungsten carbide and tungsten hexafluoride derivatives.

Safety Considerations: WF6 is highly toxic and corrosive. It can cause severe burns upon contact with the skin and eyes. Inhalation or ingestion of the gas or its decomposition products can be harmful. Proper safety precautions, such as handling the compound in a well-ventilated area and using appropriate protective equipment, should be followed.

Environmental Impact: Tungsten hexafluoride is not considered an environmental hazard. However, its reactivity and potential for releasing toxic fluorine compounds upon decomposition make proper storage, handling, and disposal important to prevent contamination.

Regulations: The use and handling of WF6 may be subject to regulations and restrictions in various countries due to its toxicity and potential environmental impact. Compliance with local regulations and guidelines is necessary.

Product Spec:

Tungsten Hexafluoride WF6 GAS

CAS No.: 7783-82-6 EINECS No.: 232-029-1 UN No.: UN2196 Purity: 99.999% Dot Class: 2.3 Appearance: Colorless

Grade Standard: Electron Grade, Industrial Grade

The COA of Product:

O2 ppm <0.5 <0.01 N2 ppm <1 0.03 CO ppm <0.5 <0.02 CO2 ppm <0.5 <0.01 SF6 ppm <0.5 <0.1 HF ppm <5 <0.19 AI ppb ≤10 <0.020 As ppb ≤10 <0.001 B ppb ≤10 <0.001 B ppb ≤10 <0.005 Ca ppb ≤5 <0.200 Cd ppb ≤2 <0.001 Cr ppb ≤10 <0.020 Fe ppb ≤10 <0.007 K ppb ≤5 <0.100 Mn ppb ≤5 <0.001 Na ppb ≤0.1 <0.001 Na ppb ≤10 <0.002 U ppb ≤10 <0.002 U ppb <t< th=""><th>Test items</th><th>Units</th><th>Quality requirements</th><th>Test results</th></t<>	Test items	Units	Quality requirements	Test results
N2 ppm <1 0.03 CO ppm <0.5 <0.02 CO2 ppm <0.5 <0.01 SiF4 ppm <0.5 <0.1 SF6 ppm <0.5 <0.1 HF ppm <5 <0.19 Al ppb ≤10 <0.020 As ppb ≤10 <0.001 B ppb ≤10 <0.005 Ca ppb ≤5 <0.200 Cd ppb ≤2 <0.001 Cr ppb ≤10 <0.020 Fe ppb ≤10 <0.007 K ppb ≤5 <0.100 Mn ppb ≤5 <0.040 Th ppb ≤0.1 <0.001 Na ppb ≤10 <0.002 Li ppb ≤10 <0.002 U ppb ≤10 <0.002 U ppb ≤10 <0.001 Pb ppb ≤10 <0.0001 <	CF4	ppm	< 0.5	< 0.01
CO	02	ppm	< 0.5	< 0.01
CO2	N2	ppm	<1	0.03
SiF4 ppm <0.5 <0.1 SF6 ppm <0.5 <0.1 HF ppm <5 <0.19 AI ppb ≤10 <0.020 As ppb ≤10 <0.001 B ppb ≤10 <0.005 Ca ppb ≤5 <0.200 Cd ppb ≤2 <0.001 Cr ppb ≤10 <0.020 Fe ppb ≤10 <0.007 K ppb ≤5 <0.100 Mn ppb ≤10 <0.001 Na ppb ≤5 <0.040 Th ppb ≤10 <0.002 Li ppb ≤10 <0.002 U ppb ≤10 <0.005 Si ppb ≤10 <0.001 Pb ppb ≤10 <0.001 Pb ppb ≤10 <0.000 Ni ppb ≤20 <0.300 Mg ppb ≤5 <0.005 <	CO	ppm	< 0.5	< 0.02
SF6 ppm <0.5	CO2	ppm	< 0.5	< 0.01
HF	SiF4	ppm	< 0.5	<0.1
AI	SF6	ppm	< 0.5	<0.1
As ppb ≤10 <0.001 B ppb ≤10 <0.005 Ca ppb ≤5 <0.200 Cd ppb ≤2 <0.001 Cr ppb ≤10 <0.020 Fe ppb ≤10 <0.007 K ppb ≤5 <0.100 Mn ppb ≤10 <0.001 Na ppb ≤5 <0.040 Th ppb ≤0.1 <0.001 Ti ppb ≤10 <0.002 Li ppb ≤10 <0.002 U ppb ≤10 <0.005 Si ppb ≤10 <0.0005 Si ppb ≤10 <0.001 Pb ppb ≤10 <0.001 Pc ppb ≤2 <0.300 Mg ppb ≤10 <0.005 Ni ppb ≤5 <0.005 Mo ppb ≤5 <0.005	HF	ppm	<5	0.19
B	Al	ppb	≤10	< 0.020
Ca ppb ≤5 <0.200	As	ppb	≤10	< 0.001
Cd ppb ≤2 <0.001 Cr ppb ≤10 <0.020 Fe ppb ≤10 <0.007 K ppb ≤5 <0.100 Mn ppb ≤10 <0.001 Na ppb ≤5 <0.040 Th ppb ≤0.1 <0.001 Ti ppb ≤10 <0.002 Li ppb ≤10 <0.002 U ppb ≤0.05 <0.001 Zn ppb ≤10 <0.005 Si ppb ≤10 <0.005 Si ppb ≤10 <0.001 Pb ppb ≤10 <0.000 Ni ppb ≤20 <0.030 Cu ppb ≤5 <0.005 Mo ppb ≤10 <0.005	В	ppb	≤10	< 0.005
Cr ppb ≤10 <0.020	Ca	ppb	≤5	<0.200
Fe ppb ≤10 <0.007	Cd	ppb	≤2	< 0.001
K ppb ≤5 <0.100	Cr	ppb	≤10	< 0.020
Mn ppb ≤10 <0.001	Fe	ppb	≤10	< 0.007
Na ppb ≤5 <0.040	K	ppb	≤5	< 0.100
Th ppb ≤0.1 <0.001	Mn	ppb	≤10	< 0.001
Ti ppb ≤10 <0.002	Na	ppb	≤5	< 0.040
Li ppb ≤10 <0.002	Th	ppb	≤0.1	< 0.001
U ppb ≤0.05 <0.001 Zn ppb ≤10 <0.005 Si ppb ≤10 <0.100 Pb ppb ≤10 <0.001 P ppb ≤2 <0.300 Mg ppb ≤10 <0.020 Ni ppb ≤20 <0.030 Cu ppb ≤5 <0.005 Mo ppb ≤10 <0.001	Ti	ppb	≤10	<0.002
Zn ppb ≤10 <0.005	Li	ppb	≤10	
Si ppb ≤10 <0.100	U	ppb	≤0.05	< 0.001
Pb ppb ≤10 <0.001	Zn	ppb	≤10	< 0.005
P ppb ≤2 <0.300	Si	ppb	≤10	<0.100
Mg ppb ≤10 <0.020	Pb	ppb	≤10	< 0.001
Ni ppb ≤20 <0.030	P	ppb	≤2	< 0.300
Cu ppb ≤5 <0.005	Mg	ppb	≤10	<0.020
Mo ppb ≤10 <0.001	Ni	ppb	≤20	< 0.030
• • • • • • • • • • • • • • • • • • • •	Cu	ppb		
Total impurities of other metal ppb ≤500 <0.0010	Мо			
	Total impurities of other metal	l ppb	≤500	<0.0010

Detailed Photos



Company Profile



Shanghai Kemike Chemical Co., Ltd is staffed by trained personnel, combine many years experience in Gas industry .We supply cylinder gas, electronic gas, etc., and the gas holder, panel, valves and fittings and other equipment, parts and engineering services to our customers in China and worldwide; The products are involved in various industrial fields, such as semiconductor chip, solar cell, LED, TFT-LCD, optical fiber, glass, laser, medicine, etc., Our mission is to partner with our global customers to provide support, solutions and quality products that are innovative, reliable, and safe. Our products mainly include: H2, O2, N2, Ar, CO2, propane, acetylene, helium, laser mixed gas, SiH4, Sih2cl2, SiHCL3, SiCL4, NH3, CF4, NF3, SF6, HCL, N2O, doping mixed gas (TMB, PH3, B2H6) and other electronic gases.

SiCl4 NH3	NH3	CH3F SiH4 Kr H2S WF6	F6+CI2
4MS C3F8	C3F8	TEOS CH4 PH3 SF6 C2	HCI+Ne
CF4 C4F8	SiH2		TMB+H2
SiF4 C3H8	CI2		He +As
BBr3 C3H6	DCE		Ge+Se
POCI3 N2	SO2		D+B
BCI3 D2	CO2		CO+NO
SiHCI3 CH2F2	HF	AsH3 C2H4 C2H2 HBr COS	Ar+O2
TMAI DMZn	DEZn	GeH4 C2H6 B2H6 H2Se GeCl4	Xe+NO







Our Advantages

- 1. Fast delivery;
- 2. Stable raw material source;
- 3. On-line analysis system for quality control in every step;
- 4. High requirement and meticulous process for handling cylinder before filling;

Our carbon monoxide have been exported to many countries like India, Pakistan, Malaysia, Indonesia, Australia, Singapore, Maldives and Ecuador.

Since the establishment of our company, it has received universal praise by virtue of good reputation, high quality and perfect after service.

FAQ

1. Q: Are you a factory or a trading company?

A: We are a manufacture and trade integration company. Expert R&D department and sophisticated supply chain is our key of success.

2. Q: Are bulk orders and multiple product orders available?

A: Yes, we have a strong production supply system to make sure all of your requirements satisfied. One station product solution is our aim of service.

3. Q: What if I never imported this product before, how do I do it?

A: Don't worry. We have import and export experience with over 50 countries over the world, our fulfillment department will guide you every step of the process.

4. What is the MOQ?

Different products have different min order. It's depends on the kind the gas and the cylinder specifications. Please feel free to contact with me directly for your requirement.

5. Q: Why choice us Kemike Gas?

A: Stable Supply, Professional Solution, Reasonable Price, and Safety Business with our Taiyu.

6. Q: 3. How does your factory do the quality control?

- A: We have standard quality control procedure.
- a> In production, we have quality analysis system to make sure each step is qualified.
- b> Before filling, we do the pre-treatment for the cylinders to clean well.
- c> After filling, we will do 100% inspection analyze before delivery.

7. Q:ls it possible to ship by air?

A:Gases are classified into class 2.1, class 2.2 and class 2.3 which are inflammable gas, non-flammable gas and poisonous gas. According to regulation, inflammable gas and poisonous gas cannot be shipped by air, and only non-flammable gas can be transported by air. If the amount purchased is large, sea transportation is better.

8. Q:Can I customize the package?

A:Yes of course! The most regular package is cylinder. Its size, color, valve, design and other requirements can all be met.

9. Q: What is the package & storage details?

A:Seamless steel cylinder with different valves, or as to your requirement.

Stored in shady, cool, dry, ventilated warehouse, and keep away from sunlight and ramming.

10. More question.....

Feel free to contact us, you will get immediately reply





+86 18762990415



williamchen@cmc-chemical.com



@ gascylindertank.com