



Good Price Semiconductor Industry Wf6 Cylinder Gas Tungsten Hexafluoride

Our Product Introduction

for more products please visit us on gascylindertank.com

Basic Information

- Place of Origin: China
- Brand Name: CMC
- Certification: COA
- Model Number: Wf6
- Minimum Order Quantity: 1 Piece
- Price: US \$ 15/PC
- Packaging Details: Cylinder/Tank
- Delivery Time: 15 days
- Payment Terms: L/C, T/T
- Supply Ability: 200 Tons/Year



Product Specification

- Product Name: Tungsten Hexafluoride
- Purity: 99.999%
- Transport: By Sea
- Appearance: Colorless
- Transport Package: 10L 40L 50L
- Specification: 10L 40L 50L
- Trademark: CMC
- Origin: China
- HS Code: 2812190091
- Supply Ability: 200t/Year
- CAS No.: 7783-82-6
- Formula: Wf6
- EINECS: 232-029-1
- Constituent: Industrial Pure Air
- Grade Standard: Electronic Grade



More Images



Product Description

Product Description

Tungsten hexafluoride (WF6) is a chemical compound composed of one tungsten atom and six fluorine atoms. It is a colorless, toxic, and corrosive gas at room temperature and pressure. Here are some key points about tungsten hexafluoride gas:

Chemical Formula: WF6

Molecular Weight: 297.84 g/mol

Physical Properties: Tungsten hexafluoride is a dense gas that is heavier than air. It has a boiling point of 17.1 °C (62.8 °F) and a melting point of -2.8 °C (27 °F) at standard atmospheric pressure.

Toxicity: WF6 is highly toxic and corrosive. It can cause severe burns and eye damage upon contact. Inhalation of the gas can lead to respiratory distress and lung damage.

Reactivity: Tungsten hexafluoride is a strong oxidizing agent and reacts readily with many substances, including water, organic compounds, and metals. It reacts violently with water, releasing highly corrosive hydrofluoric acid (HF) fumes.

Uses: WF6 is primarily used in the semiconductor industry for the deposition of tungsten films during the fabrication of integrated circuits. It is also employed as a precursor in the production of tungsten metal and other tungsten compounds.

Safety Precautions: Handling tungsten hexafluoride requires strict safety measures. It should be stored and used in a well-ventilated area with appropriate chemical handling equipment, such as fume hoods and protective gloves. Personal protective equipment, such as goggles and respiratory protection, should be worn when working with WF6.

It's important to note that tungsten hexafluoride gas is highly hazardous and should only be handled by trained professionals in controlled laboratory or industrial settings.

Product Spec:

Tungsten Hexafluoride WF6 GAS

CAS No.: 7783-82-6

EINECS No.: 232-029-1

UN No.: UN2196

Purity: 99.999%

Dot Class: 2.3

Appearance: Colorless

Grade Standard: Electron Grade, Industrial Grade

The COA of Product:

Test items	Units	Quality requirements	Test results
CF4	ppm	<0.5	<0.01
O2	ppm	<0.5	<0.01
N2	ppm	<1	0.03
CO	ppm	<0.5	<0.02
CO2	ppm	<0.5	<0.01
SiF4	ppm	<0.5	<0.1
SF6	ppm	<0.5	<0.1
HF	ppm	<5	0.19
Al	ppb	≤10	<0.020
As	ppb	≤10	<0.001
B	ppb	≤10	<0.005
Ca	ppb	≤5	<0.200
Cd	ppb	≤2	<0.001
Cr	ppb	≤10	<0.020
Fe	ppb	≤10	<0.007
K	ppb	≤5	<0.100
Mn	ppb	≤10	<0.001
Na	ppb	≤5	<0.040
Th	ppb	≤0.1	<0.001
Ti	ppb	≤10	<0.002
Li	ppb	≤10	<0.002
U	ppb	≤0.05	<0.001
Zn	ppb	≤10	<0.005
Si	ppb	≤10	<0.100
Pb	ppb	≤10	<0.001
P	ppb	≤2	<0.300
Mg	ppb	≤10	<0.020
Ni	ppb	≤20	<0.030
Cu	ppb	≤5	<0.005
Mo	ppb	≤10	<0.001
Total impurities of other metal	ppb	≤500	<0.0010

Detailed Photo



WF6





Shanghai Kemike Chemical Co., Ltd is staffed by trained personnel, combine many years experience in Gas industry .We supply cylinder gas, electronic gas, etc ., and the gas holder, panel, valves and fittings and other equipment, parts and engineering services to our customers in China and worldwide; The products are involved in various industrial fields, such as semiconductor chip, solar cell, LED, TFT-LCD, optical fiber, glass, laser, medicine , etc.,. Our mission is to partner with our global customers to provide support, solutions and quality products that are innovative, reliable, and safe.

Our products mainly include: H₂, O₂, N₂, Ar, CO₂, propane, acetylene, helium, laser mixed gas, SiH₄, SiH₂Cl₂, SiHCl₃, SiCl₄, NH₃, CF₄, NF₃, SF₆, HCL, N₂O, doping mixed gas (TMB, PH₃, B₂H₆) and other electronic gases.


SiCl ₄	NH ₃	NH ₃	CH ₃ F	SiH ₄	Kr	H ₂ S	WF ₆	F ₆ +Cl ₂
4MS	C ₃ F ₈	C ₃ F ₈	TEOS	CH ₄	PH ₃	SF ₆	C ₂	HCl+Ne
CF ₄	C ₄ F ₈	SiH ₂						TMB+H ₂
SiF ₄	C ₃ H ₈	Cl ₂						He +As
BBr ₃	C ₃ H ₆	DCE						Ge+Se
POCl ₃	N ₂	SO ₂						D+B
BCl ₃	D ₂	CO ₂						CO+NO
SiHCl ₃	CH ₂ F ₂	HF						Ar+O ₂
TMAI	DMZn	DEZn						Xe+NO
			AsH ₃	C ₂ H ₄	C ₂ H ₂	HBr	COS	
			GeH ₄	C ₂ H ₆	B ₂ H ₆	H ₂ Se	GeCl ₄	



 **Shanghai Kemike Chemical Co.,Ltd**

 +86 18762990415

 williamchen@cmc-chemical.com

 gascylindertank.com